

The Top Down™ 80 BoilerMate™

The industry's best performing, most efficient 80-gallon indirect water heater.



Get behind the wheel of the new Top Down™ 80 BoilerMate™. All piping and wiring connections are on top for lightning fast installation and easy service. The low profile makes handling a breeze and fits nearly any space. Your customers get the power and performance of an 80-gallon water heater with the fuel savings that only an AMTROL® BoilerMate™ indirect can provide. Visit your AMTROL® supplier today.

Test Drive the Top Down™ 80.



 **AMTROL** INC.
www.amtrol.com

BoilerMate™ Top Down™ 80 Specifications

Dimensions

Model Number	Capacity (gallons)	Height (inches)	Diameter (inches)	Shipping Weight (lbs.)	Cold Water inlet-nptm	Hot Water outlet-nptf	Boiler Supply	Boiler Return	Control
TD-80Z	80	58	26	190	3/4"	3/4"	3/4" NPTM	3/4" NPTM	Dial
TD-80L	80	58	26	190	3/4"	3/4"	3/4" NPTM	3/4" NPTM	Digital



Domestic Water Performance

BOILER OUTPUT (5 gpm input-to BoilerMate™)	1	2
	FIRST-HOUR RATING (90° F rise)	CONTINUOUS FLOW (70° F rise steady state)
BTU/HR	GPH	GPH
40,000	120	69
60,000	147	104
80,000	174	139
100,000	201	173
120,000	228	208
140,000	255	242



All models include a 5-year upgradeable warranty.

Limited Lifetime upgrade is available through your BoilerMate™ distributor.



www.amtrol.com

Corporate Headquarters

1400 Division Road, West Warwick, RI 02893
Telephone: 401-884-6300 • Fax: 401-884-5276

AMTROL Canada, Ltd.

275 Shoemaker Street, Kitchener, Ontario N2E 3B3
Telephone: 519-748-1138 • Fax: 519-748-4231